



SPECIFICATIONS	
article number	150.032.073
max. working pressure	720 bar
max. spreading force	161 kN / 16.4 t
max. pulling force	49.5 kN / 5.1 t
spreading / pulling stroke	250 mm
number of plungers	1
retracted length	512 mm
max. length	762 mm
weight, ready for use	12.4 kg
dimensions (LxWxH)	512x122x318 mm
temperature reach	-20° + 80° C
required oil contents	397 cc (effective)

ACCESSORIES	Art.no.
maintenance set, OS 3321+	150.033.357
cross head	150.033.032
V-base	150.181.324
wedge tip	150.181.325
flat base	150.181.326
set pulling head	150.582.281
set pulling chains length 4.5 m	150.582.152
connection piece	150.581.327
extension pipe 165 mm	150.181.321
extension pipe 330 mm	150.181.322
extension pipe 600 mm	150.181.323
RAM support HRS22	150.181.011
rim adapter	150.182.580
swivel head	150.181.329

NORMS	TESTED	CLASS
prEN 13204	✓	R161/250-12.4
DIN 14751-T3	✓	RZ 512/762
NFPA 1936	✓	

SAFETY FACTORS / TESTS
Safety factor tool, hydraulic: 2 x 720 bar = 1440 bar
Safety factor hoses: 4 x 720 bar = 2880 bar
Endurance test deadman's handle: 6000 cycles
Endurance test tool: 1000 cycles of opening and closing while plunger is loaded with max. force at 720 bar.

Manufacturing sales & service worldwide

Holmatro Rescue Equipment
P.O. Box 33, 4940 AA Raamsdonksveer
The Netherlands
tel.: + 31 (0)162 - 58 92 00
fax: + 31 (0)162 - 52 24 82
e-mail: info@holmatro.com
homepage: www.holmatro.com

Manufacturing sales & service U.S.A., Canada and Latin America

Holmatro, Inc.
505 McCormick Drive, Glen Burnie, MD
21061
U.S.A.
tel.: + 1 - 410 - 768 - 9662
fax: + 1 - 410 - 768 - 4878
e-mail: info@holmatro-usa.com

© Holmatro® 0203

All information provided herein was carefully examined. We assume no liability however for any mistakes or incompleteness. Subject to error, revision and technical modifications

